



Designed for:	Attaching Friction Stays to Reinforced PVCU
Head Style:	Shallow Pan
Drive Bit:	PH2
Thread Form:	Spaced Self-Tapping
Point:	Drill Point
Coating:	Inorganic Anti-Corrosion Coating
Salt Spray Testing:	3000 Hours in accordance with BS EN 9227:2012
Corrosion Protection:	Grade 5 acc. to BS EN 1670:2007
Shank Material:	Martensitic Stainless Steel
Material Grade:	410
Effective Thread Length:	Fully Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
SSR 3.9 x 16 S	3.9mm x 16.0mm	8.10mm ± 0.20mm	1000
SSR 3.9 x 19 S	3.9mm x 19.0mm	8.10mm ± 0.20mm	1000
SSR 3.9 x 25 S	3.9mm x 25.0mm	8.10mm ± 0.20mm	1000
SSR 3.9 x 28 S	3.9mm x 28.0mm	8.10mm ± 0.20mm	1000



Rapierstar Limited  
Star Business Park, Macclesfield, Cheshire SK11 9JA  
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399  
email: [info@rapierstar.com](mailto:info@rapierstar.com)

[www.rapierstar.com](http://www.rapierstar.com)

